

FARM-MAXX

FTM, FTH, and FTX Series Gear Drive Tillers

Dependable Rugged Gear Drive Performance From 48 to 80 Inches



Farm-Maxx Gear Drive Rotary Tillers are built tough for years of dependable, top notch service and are popular with landscapers, gardeners, nursery and orchard operators, developers, and small farmers.

5 Models are offered with working widths from 48 to 80 inches. All models feature heavy duty gear drive transmissions for rugged performance even under the most demanding conditions.

	FTM-48G	FTM-60G	FTH-66G	FTH-74G	FTX-80G
Specifications					
Working Width (In.)	48	60	66	74	80
Working Depth (In.)	7	7	7	7	8
Blades / Flange	6	6	6	6	6
Total Blades	36	42	48	54	60
Side Drive	Gear	Gear	Gear	Gear	Gear
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat 0/Cat I	Cat 0/Cat I	Cat I/Cat II	Cat I/Cat II	Cat I/Cat II
PTO Shaft Series	4	4	5	5	6
PTO Power Required (HP)	15-35	15-35	30-50	30-50	35-60
Optimum PTO Speed(RPM)	540	540	540	540	540
Rotor Speed (RPM)	246	253	242	242	235
Rotor Flange Diameter (In.)	6.3	6.3	7.4	7.4	9.5
Rotor Flange Thickness (In.)	0.39	0.39	0.47	0.47	0.51
Approximate Weight W/PTO (LBS)	440	490	676	722	973

- Six Tines Per Flange
- Series 4-5 and 6 Eurocardan PTO Shafts with Slip Clutch are Standard
- Heavy Duty Welded Hitch Plates Offer Multiple Attachement Options
- Automotive Quality Powder Coat Paint Finish
- Heavy Duty Zinc Plated Jack Stand
- Super Heavy Drag Board with Zinc Plated Check Chain