

T10 Series Rotary Tillers

Tiller Models from 58 to 74 Inches. The Heavy Duty Choice for Demanding Applications



Slightlier heavier than the T5 Series, the T10 Series Rotary Tillers from Phoenix are made to fit tractors from 30-50 horsepower. Available in either chain drive or gear drive, these units will give you years of trouble free operation under the most demanding applications.

Standard Features Include:

- Six Tines Per Flange
- Adjustable Lower Links
- Drive Housing Oil Level Site Glass on Chain Drive Models (Not available on gear drive)
- Multi-position Heavy Duty Zinc Plated Jack Stand
- Powder Coat Paint Finish Available in Orange Or Red
- Heavy Duty Adjustable Drag Board W/Zinc Plated Check Chain
- Standard Eurocardan Series 5 PTO With Slip Clutch
- Heavy Duty Construction with Double Torque Tube and Single Piece Welded Center Hitch

				00-	00	(a)	
<u>Specifications</u>	<u>T10-58</u>	T10-66	<u>T10-74</u>	T10-58GE	T10-66GE	T10-74GE	
Working Width (In.)	58	66	74	58	66	74	
Working Depth (In.)	7	7	7	7	7	7	
Blades / Flange	6	6	6	6	6	6	
Total Blades	42	48	54	42	48	54	
Side Drive	#100 Chain	#100 Chain	#100 Chain	Gear	Gear	Gear	
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	
Hitch	Cat 1	Cat 1	Cat 1	Cat 1	Cat 1	Cat 1	
PTO Shaft Series	5	5	5	5	5	5	
PTO Power Required (HP)	50	50	50	50	50	50	
Optimum PTO Speed(RPM)	540	540	540	540	540	540	
Rotor Flange Diameter (In.)	6.3	6.3	6.3	6.3	6.3	6.3	
Rotor Flange Thickness (In.)	0.5	0.5	0.5	0.5	0.5	0.5	
Approximate Weight W/PTO (LBS)	624	657	690	646	679	712	