







## T30 Series Rotary Tillers

The sturdy frame, steel plate box-type bonnet and the 3 speed side drive in oil bath make the T30 Series from Phoenix Line extremely reliable and suitable for any type of soil. Standard features include: Series 8 PTO drive line with 4 plate slip clutch for the ultimate in driveline protection, 6 tines per flange, 2+2 speed gearbox, gear drive final transmission.

From the oversized rotor tube with the optional double flange to the double extended torque tubes, this machine is built to give you years of trouble free service.

### T30 Series 90-160 HP

				
<b>Specifications</b>	<b><u>T30-90GE</u></b>	<b><u>T30-100GE</u></b>	<b><u>T30-112GE</u></b>	<b><u>T30-120GE</u></b>
Working Width (In.)	90	100	112	120
Working Depth (In.)	7	7	7	7
Blades / Flange	6	6	6	6
Total Blades	48	54	60	60
Side Drive	Gear	Gear	Gear	Gear
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat II & III	Cat II and III	Cat II and III	Cat II and III
PTO Shaft Series	8	8	8	8
PTO Power Required (HP)	90-160	90-1960	90-160	90-160
Optimum PTO Speed(RPM)	540	540	540	540
Rotor Flange Diameter (In.)	6.3	6.3	6.3	6.3
Rotor Flange Thickness (In.)	0.6	0.6	0.6	0.6
Approximate Weight W/PTO (LBS)	2515	2725	2879	3108
Rotor Speeds	4+2	4+2	4+2	4+2

Get the most out of your T30 Series Rotary Tiller by adding options including: roller packer, hydraulic kit for roller adjustment, and double flanged rotor tube.

### Accessories for 30 Series Tillers

<b><u>T30-RP</u></b>	<b><u>T30-HP</u></b>	<b><u>T30-DF</u></b>
Roller Packer	Hydraulic Kit	Double Flange
For Roller Packer		